

General Information

Steel Wire Rope

Points to remember when ordering SWR:

- | | | |
|-----|----------------------------|--|
| 1. | Finish: | Ungalvanised, galvanised, stainless steel |
| 2. | Rope diameter: | 24 mm |
| 3. | Construction and type: | 6 x 36 (WS) /IWRC, 6 X 36 (WS) /FC |
| 4. | Direction and type of lay: | Right Hand Regular Lay (RHRL) |
| 5. | Length and quantity: | 1,000 m x 5 R/L |
| 6. | Lubrication: | A-1 (Petroleum), C (Asphalt) |
| 7. | Specification: | BS, JIS, EN |
| 8. | Grade of wire: | IPS, EIPS, 165 kg/mm ² , 1770 N/mm ² |
| 9. | Application: | Crane |
| 10. | Packing: | Coil, wooden reel, steel reel |
| 11. | Remarks: | Other special requirement |

Galvanised Steel Wire Strand:

- | | | |
|----|----------------------------|-------------------------------|
| 1. | Strand Diameter: | ¼ in. 7/2.00 |
| 2. | Length and quantity: | 1,000 m x 10 R/L |
| 3. | Direction and type of lay: | Right Hand Regular Lay (RHRL) |
| 4. | Specification: | ASTM A-475, BS-183 |
| 5. | Grade of wire: | EHS, 1100, Grade 1 |
| 6. | Weight of zinc coating: | Class A |

Stainless Steel Wire Rope:

- | | | |
|-----|----------------------------|--|
| 1. | Construction: | 6 x 24 /FC, 6 x 24 /IWRC |
| 2. | Grade: | AISI 302, AISI 304, AISI 305, AISI 316 |
| 3. | Rope diameter: | 24 mm, ¾ in. |
| 4. | Direction and type of lay: | Right Hand Regular Lay (RHRL) |
| 5. | Length and Quantity: | 1,000 x 1 R/L |
| 6. | Tensile strength: | 165 kg/mm ² , 1,770 N/mm ² |
| 7. | Packaging: | Wooden reel, plastic spool |
| 8. | Specification: | DIN, BS, JIS |
| 9. | Application: | Crane |
| 10. | Remarks: | Other special requirements |